

temperzone Australia Pty Ltd

ENQUIRIES

AU: sales@temperzone.com.au

NZ: nz.sales@temperzone.com

AUSTRALIA

Sydney: (02) 8822 5700

Melbourne: (03) 8769 7600

Brisbane: (07) 3308 8333

Adelaide: (08) 8115 2111

DISTRIBUTORS

Newcastle: (02) 4962 1155

Perth: (08) 6399 5900

Launceston: (03) 6331 4209

NEW ZEALAND

Auckland: (09) 279 5250

Wellington: (04) 569 3262

Christchurch: (03) 379 3216



WARRANTY

Must be maintained in accordance with maintenance recommendations.

hitachiaircon.com.au

hitachiaircon.co.nz



The specifications of this catalogue may change without prior notice to allow Hitachi Cooling & Heating to incorporate the latest innovations for its customers. The information contained in this catalogue is merely informative. Hitachi Cooling & Heating declines any responsibility in the broadest sense, for damage, direct or indirect, arising from the use and / or interpretation of the recommendations in this catalogue.

RCI-3.0FSN3 / RAS-3HVNC	RCI-4.0FSN3 / RAS-4HVNC1	RCI-5.0FSN3 / RAS-5HVNC1	RCI-6.0FSN3 / RAS-6HVNC1
7.1 3.2 - 8.0 8.0 3.5 - 10.6	10.0 4.5 - 11.2 11.2 5.0 - 14.0	12.5 5.7 - 14.0 14.0 5.0 - 18.0	13.0 6.0 - 16.0 16.0 5.0 - 20.0
3.48 / 3.33 3.70 / 3.52	3.72 / 3.55 4.51 / 4.25	3.29 / 3.12 3.84 / 3.63	3.15 / 3.00 3.61 / 3.44
450 / 383 / 300 / 233	617 / 517 / 400 / 333	617 / 550 / 443 / 350	617 / 583 / 467 / 367
298 x 840 x 840 600 x 792 x 300 26 / 44	298 x 840 x 840 1140 x 950 x 370 26 / 79	298 x 840 x 840 1140 x 950 x 370 26 / 89	298 x 840 x 840 1140 x 950 x 370 26 / 89
42 / 36 / 32 / 28 48 / 50 / 46	48 / 43 / 39 / 33 52 / 54 / 50	48 / 45 / 40 / 35 52 / 54 / 50	48 / 46 / 41 / 37 55 / 57 / 53
-5° / 46°C -20° / 15°C P-AP160NA1 (Std - Exc Motion Sensor) / P-AP160NAE (Optional - Inc Motion Sensor) PC-ARF PC-AWR / PC-ALH3 PI-160LS1 PD-75A PCC-1A			
9.52 / 15.88 50 20	9.52 / 15.88 70 30	9.52 / 15.88 75 30	9.52 / 15.88 75 30
30 Flare Nut / Flare Nut			
AC 1 Ph 220 - 240V 50Hz			
16	26.3	26.4	26.4

1 metre from the unit service cover surface, and 1.5 metres from floor level. Voltage of the power source for the indoor fan motor is 220V. The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.