

Kaze Plus Tech Data

DESCRIPTION		UNIT	KAZE PLUS				
Details							
Tonnage Class	TR	1.0TR	1.0TR	1.5TR	1.5TR	2.0TR	
Star Rating		5	3	3	5	2	
Model Number		RAW511HEDO	RAW312HEDO	RAW318HFDO	RAW518HEDO	RAW222KVD	
Compressor	Type	ROTARY-R32	ROTARY-R32	ROTARY-R32	ROTARY-R32	ROTARY-R22	
Performance							
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	
Rated Capacity - Cooling/Heating	BTU/Hr	12000	11260	17402	18000	21019	
Rated Capacity - Cooling/Heating ISEER	Watts	3517	3300	5100	5275	6160	
		3.45	3.00	3.09	3.60	2.75	
Annual Power Consumption (As per BEE Normms)	Kwh	789.14	851.52	1277.28	1134.28	1734.00	
Fan Speed	Steps	3	3	3	3	3	
Sound Level*	dB	50	46	50	50	52	
Air Flow (Super High) - Cooling / Heating	CFM	400	295	450	450	470	
Electrical							
Rated Power Input - Cooling/Heating	Watts	1019	1100	1650	1465	2240	
Current Drawn - Cooling / Heating	Amps	4.7	4.9	7.55	6.7	9.9	
Advanced Features							
Remocon	Type	Wireless	Wireless	Wireless	Wireless	Wireless	
Kaimin							
Filter Clean Indicator		✓		✓	✓	✓	
On/Off Timer with Advance Start Up		✓	✓	✓	✓	✓	
Auto Power Save Mode		✓		✓	✓	✓	
Wireless LCD Remote with Backlight		✓	✓	✓	✓	✓	
Key Features							
Kaimin - Cooling & Heating							
Defrosting Sensor							
Auto Restart		✓	✓	✓	✓	✓	
Digi Lock			✓				
Auto Fan Speed		✓	✓	✓	✓	✓	
Silent Mode		✓		✓	✓	✓	
Auto Climate Technology							
Precoated Alluminum Fins		✓		✓	✓	✓	
Dimensions							
Dimension (WXHXD)	mm	660 X 430 X 755	560X377X615	660 X 430 X 755	660 X 430 X 755	660 X 430 X 755	
Net Weight	Kg	52	40	60	62	64	

Notes:
Features may vary from model to model.
*At Super Silent fan speed & at a distance of 1 m.
Hitachi Air Conditioners are designed to work in ambient temperature up to 52°C.
Due to continuous research & development, specifications, features and look may change without prior notice.

Kaze Reidan Tech Data

DESCRIPTION	UNIT	KAZE REIDAN
Details		
Tonnage Class	TR	1.5TR
Star Rating		2
Model Number		RAW218KYH
Compressor	Type	ROTARY-R22
Performance		
Rated Power Supply	Volts/Hz/Phase	230/50/1
Rated Capacity - Cooling/Heating	BTU/Hr	17000 / 17300
Rated Capacity - Cooling/Heating	Watts	4982 / 5069
ISEER		2.80
Annual Power Consumption (As per BEE Normms)	Kwh	-
Fan Speed	Steps	3
Sound Level*	dB	50
Air Flow (Super High) - Cooling / Heating	CFM	420 / 420
Electrical		
Rated Power Input - Cooling/Heating	Watts	1780 / 1755
Current Drawn - Cooling / Heating	Amps	7.9 / 7.8
Advanced Features		
Remocon	Type	Wireless
Kaimin		✓
Filter Clean Indicator		✓
On/Off Timer with Advance Start Up		✓
Auto Power Save Mode		✓
Wireless LCD Remote with Backlight		✓
Key Features		
Kaimin - Cooling & Heating		✓
Defrosting Sensor		✓
Auto Restart		
Digi Lock		✓
Auto Fan Speed		✓
Silent Mode		✓
Auto Climate Technology		✓
Precoated Alluminum Fins		✓
Dimensions		
Dimension (WXHXD)	mm	660 X 430 X 735
Net Weight	Kg	62

Notes:
Features may vary from model to model.
*At Super Silent fan speed & at a distance of 1 m.
Hitachi Air Conditioners are designed to work in ambient temperature up to 52°C.
Due to continuous research & development, specifications, features and look may change without prior notice.