

Model		Indoor Unit		RAS-GJ10CMS	RAS-GJ13CMS	RAS-GJ18CMS	RAS-GJ24CMS
		Outdoor Unit		RAC-GJ10CMS	RAC-GJ13CMS	RAC-GJ18CMS	RAC-GJ24CMS
System	Power Supply	V/ Hz/ ϕ		1ϕ, 50Hz, 220~240V			
	Cooling Capacity	Rated (Min-Max)	kW	2.6 (0.9 - 3.6)	3.6 (0.9 - 4.2)	5.3 (0.9 - 6.5)	6.5 (1.5 - 8.8)
			Btu/hr	3,070 - 12,200	3,070 - 14,300	3,070 - 22,100	5,110 - 30,000
	Running Current	A		3.45	4.28	6.26	7.94
Indoor	Air Flow (H/M/L/Silent)	CMH		510 / 420 / 300 / 180	630 / 480 / 330 / 210	870 / 720 / 480 / 360	1020 / 840 / 600 / 480
	Indoor Sound Level (H/M/L/Silent)	dB (A)		41 / 32 / 24 / 19	43/33/27/19	48/40/33/30	48 / 42/ /36/ 30
	Net Dimensions	W x H x D (mm)		780 x 280 x 230	780 x 280 x 230	900 x 300 x 230	1100 x 300 x 260
	Net Weight	Kg		8	8	10	15
	Dehumidifying Capacity	l/h		1.4	1.6	3.4	4.5
Outdoor	Refrigerant/ Compressor Type	R32/ DC Inverter					
	Outdoor Sound Level	dB (A)		50	50	52	52
	Net Dimensions	W x H x D (mm)		658 x 530 x 275	750 x 570 x 280	850 x 650 x 298	850 x 745 x 298
	Net Weight	Kg		21	30	39	46
Piping Connections	Liquid pipe Size	mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	
	Gas Pipe Size		9.52 (3/8")	9.52 (3/8")	12.7 (1/2")	15.88 (5/8")	
	Maximum length of piping	m		20	20	20	30
	Maximum height of piping	m		10	10	10	20