

Primary Cassette			RCI-3.0UFE1NH	RCI-3.5UFE1NH	RCI-4.0UFE1NH	RCI-5.0UFE1NH	RCI-6.0UFE1NH	RCI-6.5UFE1NH
Nominal Capacity (min - max)	Cooling	KW	7,00 (2,40-7,85)	8,70 (4,00-9,20)	10,10 (3,50-11,00)	12,10 (3,30-13,20)	13,89 (3,40-16,20)	16,90 (3,30-18,00)
	Heating	KW	8,25 (2,10-8,80)	9,00 (3,50-9,50)	11,20 (3,32-12,00)	13,50 (3,00-14,60)	16,53 (3,70-18,00)	19,49 (3,00-21,00)
Seasonal energy rating	Cooling		A++	A++	A++	A+	A+	A+
	Heating		A+	A+	A	A	A	A
SEER			6,73	6,10	6,10	6,05	5,64	5,60
SCOP			4,33	4,20	3,92	3,98	3,81	3,87
EER - COP			3.66 - 4.06	3.21 - 4.00	2.72 - 3.20	2.85 - 3.65	2.89 - 3.51	2.51 - 2.89
Sound Pressure (low - med - high)		dB(A)	37-42-45	42-46-48	42-45-50	47-49-51	42-45-51	42-45-52
Sound Power (Eurovent data)		dB(A)		59	62	65	64	65
Air flow (low - med - high)		m3/h	720-980-1180	900-1120-1400	1000-1300-1600	1550-1700-1850	1400-1700-2100	1400-1700-2100
Diameter of pipes (liquid-gas)		Inches	3/8 - 5/8	3/8 - 5/8	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4
Condensate drain diameter		mm	32	32	32	32	32	32
Remote control (standard)			Wired (Wireless)	Wired (Wireless)	Wired (Wireless)	Wired (Wireless)	Wired (Wireless)	Wired (Wireless)
Programming			7 day / 24h	7 day / 24h	7 day / 24h	7 day / 24h	7 day / 24h	7 day / 24h
Dimensions	Height	mm	248	248	248	298	298	298
	Width	mm	840	840	840	840	840	840
	Depth	mm	840	840	840	840	840	840
	Height	mm	37	37	37	37	37	37
Cassette panel dimensions	Width	mm	950	950	950	950	950	950
	Depth	mm	950	950	950	950	950	950
Weight		kg	25	27	27	32	32	32

Primary Ducts			RPIL-3.0UFE1NH	RPIH-3.5UFE1NH	RPIH-4.0UFE1NH	RPIH-5.0UFE1NH	RPIH-6.0UFE1NH	RPIH-6.5UFE1NH
Nominal Capacity (min - max)	Cooling	KW	6,90 (2,45-7,85)	8,50 (4,00-9,50)	10,10 (3,50-11,00)	12,10 (3,30-13,20)	14,19 (3,20-16,00)	17,10 (3,30-18,50)
	Heating	KW	8,30 (2,20-8,70)	9,00 (3,50-9,40)	10,50 (3,32-12,00)	13,40 (3,00-14,60)	16,13 (3,40-18,50)	18,00 (3,00-19,50)
Seasonal energy rating	Cooling		A++	A++	A++	A++	A+	A+
	Heating		A+	A+	A	A	A	A
SEER			6,29	6,20	6,10	6,28	5,94	5,81
SCOP			4,05	4,00	3,92	3,70	3,70	3,72
EER - COP			3,19-3,74	3,18-3,75	2,66-3,00	2,87 - 3,70	2,97 - 3,47	2,59 - 2,95
Sound Pressure (low - med - high)		dB(A)	31-34-38	33-38-41	38-40-42	37-40-43	42-45-47	43-45-48
Sound Power (Eurovent data)		dB(A)		61	63	65	69	77
Air flow (low - med - high)		m3/h	490-700-1000	900-1120-1450	1400-1600-1800	1300-1500-1750	1900-2200-2400	1900-2200-2400
Static Pressure Nom (min- max)		Pa	25 (0 -40)	37 (0 -120)	37 (0 -120)	50 (0 -120)	50 (0 -120)	50 (0 -120)
Diameter of pipes (liquid-gas)		Inches	3/8 - 5/8	3/8 - 5/8	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4
Condensate drain diameter		mm	32	32	32	32	32	32
Remote control (standard)			Hard Wired	Hard Wired	Hard Wired	Hard Wired	Hard Wired	Hard Wired
Programming			7 day	7 day	7 day	7 day	7 day	7 day
Dimensions	Height	mm	190	268	268	350	350	350
	Width	mm	1180	1140	1140	1300	1300	1300
	Depth	mm	447	720	720	800	800	800
Weight		kg	24	38	38	51	51	51

Primary Floor/Ceiling			RPFC-3.0UFE1NH	RPFC-3.5UFE1NH	RPFC-4.0UFE1NH	RPFC-5.0UFE1NH	RPFC-6.0UFE1NH	RPFC-6.5UFE1NH
Nominal Capacity (min - max)	Cooling	KW	6,50 (2,45-7,85)	8,60 (3,50-9,00)	9,80 (3,50-11,00)	12,10 (3,30-13,20)	13,76 (3,10-16,10)	16,30 (3,30-18,00)
	Heating	KW	7,35 (2,20-8,70)	8,70 (3,00-9,20)	10,50 (3,32-12,00)	13,50 (3,00-14,60)	16,59 (3,60-18,00)	18,00 (3,00-19,00)
Seasonal energy rating	Cooling		A+	A++	A+	A+	A	A
	Heating		A+	A+	A	A	A	A
SEER			5,81	6,10	5,87	5,70	5,33	5,30
SCOP			4,01	4,10	3,82	3,78	3,55	3,78
EER - COP			3,35-3,55	2,92-3,78	2,61-2,88	2,75 - 3,24	2,75 - 3,42	2,39 - 2,64
Sound Pressure (low - med - high)		dB(A)	44-48-51	43-48-54	51-52-54	48-51-54	46-52-58	48-53-56
Sound Power (Eurovent data)		dB(A)		65	65	65	68	75
Air flow (low - med - high)		m3/h	800-950-1100	900-1120-1450	1300-1500-1700	1600-1800-2000	1200-1600-2000	1500-1700-2000
Diameter of pipes (liquid-gas)		Inches	3/8 - 5/8	3/8 - 5/8	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4
Condensate drain diameter		mm	25	25	25	25	25	25
Remote control (standard)			Wired (Wireless)	Wired (Wireless)	Hard Wired	Hard Wired	Hard Wired	Hard Wired
Programming			7 day / 24h	7 day / 24h	24h / 7 day	24h / 7 day	24h / 7 day	24h / 7 day
Dimensions	Height	mm	230	230	230	230	230	230
	Width	mm	990	1285	1285	1580	1580	1580
	Depth	mm	680	680	680	680	680	680
Weight		kg	30	37	37	48	48	48